



- Excellent shockproof function with patent
- Totally sealed structure for use in any weather
- Exclusive closed magnetic field, magnetic damped compensator
- Reflector circular vial observation

Specification

Model	RL24	RL28	RL32
Standard Deviation for 1 Km. Double Run Leveling	2.0 mm	1.5 mm	1.0 mm
Image	Erect		
Magnification	24x	28x	32x
Objective Aperture	34 mm		
Field of View	1°20'		
Minimum Focus	0.5 m		
Multiplication Constant	100		
Additive Constant	0		
Compensator Range	+/- 15'		
Compensator Setting Accuracy	+/- 0.6"		
Sensitivity of Bubble	8' / 2 mm		
Horizontal Circle-reading	1° or 1 gon		

Ruide Surveying Instrument Co., Ltd.

Add: 2/F, Surveying Building (He Tian Bldg),
No. 26 Ke Yun Road, Tian He District,
Guangzhou 510665, CHINA
Tel. 86-20-2338-0961 Fax. 86-20-2338-0962
<http://www.ruideinstrument.com>

Thailand Authorized Distributor:

C. Intergroup Co., Ltd.

160 Soi Paholyotin 14, Paholyotin Road, Samsennai,
Payatai, Bangkok 10400
Tel. 0-2278-0002, 0-2616-7671-2 Fax. 0-2278-2435
<http://www.cintergroup.com> <http://www.cig.co.th>
e-mail: cig@cintergroup.com